

MESSAGE NO: 6327303 MESSAGE DATE: 11/22/2016
MESSAGE STATUS: Active CATEGORY: Antidumping
TYPE: PRE-Preliminary PUBLIC NON-PUBLIC
SUB-TYPE: AFF-Affirmative
FR CITE: 81 FR 79441 FR CITE DATE: 11/14/2016

REFERENCE
MESSAGE #
(s):

CASE #(s): A-580-887

EFFECTIVE DATE: 11/14/2016 COURT CASE #:
PERIOD OF REVIEW: 04/01/2015 TO 03/31/2016
PERIOD COVERED: TO

Notice of Lifting of Suspension Date:

TO: { Directors Of Field Operations, Port Directors }

FROM: { Director AD/CVD & Revenue Policy & Programs }

RE: Notice of a preliminary determination in an antidumping duty investigation of certain carbon and alloy steel cut-to-length plate from the Republic of Korea (A-580-887)

1. On 11/14/2016, Commerce published in the Federal Register its affirmative preliminary determination of sales at less than fair value and postponement of the final determination in the antidumping duty investigation of certain carbon and alloy steel cut-to-length plate from the Republic of Korea (81 FR 79441).

2. Scope of the Investigation.

The products covered by this investigation are certain carbon and alloy steel hot-rolled or forged flat plate products not in coils, whether or not painted, varnished, or coated with plastics or other non-metallic substances (cut-to-length plate). Subject merchandise includes plate that is produced by being cut-to-length from coils or from other discrete length plate and plate that is rolled or forged into a discrete length. The products covered include (1) Universal mill plates (i.e., flat-rolled products rolled on four faces or in a closed box pass, of a width exceeding 150 mm but not exceeding 1250 mm, and of a thickness of not less than 4 mm, which are not in coils and without patterns in relief), and (2) hot-rolled or forged flat steel products of a thickness of 4.75 mm or more and of a width which exceeds 150 mm and measures at least twice the thickness, and which are not in coils, whether or not with patterns in relief. The covered products described above may be rectangular, square, circular or other shapes and include products of either rectangular or non-rectangular cross-section where such non-rectangular cross-section is achieved subsequent to the rolling process, i.e., products which have been "worked after rolling" (e.g., products which have been beveled or rounded at the edges).

For purposes of the width and thickness requirements referenced above, the following rules apply:

(1) except where otherwise stated where the nominal and actual thickness or width measurements vary, a product from a given subject country is within the scope if application of either the nominal or actual measurement would place it within the scope based on the definitions set forth above unless the product is already covered by an order existing on that specific country (i.e., Certain Hot Rolled Steel Flat Products from Australia, Brazil, Japan, the Republic of Korea, the

Netherlands, the Republic of Turkey, and the United Kingdom: Amended Final Affirmative Antidumping Determination for Australia, the Republic of Korea, and the Republic of Turkey and Antidumping Duty Orders, 81 FR 67962 (October 3, 2016), and

(2) where the width and thickness vary for a specific product (e.g., the thickness of certain products with non-rectangular cross-section, the width of certain products with non-rectangular shape, etc.), the measurement at its greatest width or thickness applies.

Steel products included in the scope of this investigation are products in which: (1) iron predominates, by weight, over each of the other contained elements; and (2) the carbon content is 2 percent or less by weight.

Subject merchandise includes cut-to-length plate that has been further processed in the subject country or a third country, including but not limited to pickling, oiling, levelling, annealing, tempering, temper rolling, skin passing, painting, varnishing, trimming, cutting, punching, beveling, and/or slitting, or any other processing that would not otherwise remove the merchandise from the scope of the investigation if performed in the country of manufacture of the cut-to-length plate.

All products that meet the written physical description, are within the scope of this investigation unless specifically excluded or covered by the scope of an existing order. The following products are outside of, and/or specifically excluded from, the scope of this investigation:

(1) products clad, plated, or coated with metal, whether or not painted, varnished or coated with plastic or other non-metallic substances;

(2) military grade armor plate certified to one of the following specifications or to a specification that references and incorporates one of the following specifications:

- MIL-A-12560,
- MIL-DTL-12560H,
- MIL-DTL-12560J,
- MIL-DTL-12560K,
- MIL-DTL-32332,
- MIL-A-46100D,
- MIL-DTL-46100-E,
- MIL-46177C,
- MIL-S-16216K Grade HY80,
- MIL-S-16216K Grade HY100,

- MIL-S-24645A HSLA-80;
- MIL-S-24645A HSLA-100,
- T9074-BD-GIB-010/0300 Grade HY80,
- T9074-BD-GIB-010/0300 Grade HY100,
- T9074-BD-GIB-010/0300 Grade HSLA80,
- T9074-BD-GIB-010/0300 Grade HSLA100, and
- T9074-BD-GIB-010/0300 Mod. Grade HSLA115,

except that any cut-to-length plate certified to one of the above specifications, or to a military grade armor specification that references and incorporates one of the above specifications, will not be excluded from the scope if it is also dual- or multiple-certified to any other non-armor specification that otherwise would fall within the scope of this order;

(3) stainless steel plate, containing 10.5 percent or more of chromium by weight and not more than 1.2 percent of carbon by weight;

(4) CTL plate meeting the requirements of ASTM A-829, Grade E 4340 that are over 305 mm in actual thickness;

(5) Alloy forged and rolled CTL plate greater than or equal to 152.4 mm in actual thickness meeting each of the following requirements:

(a) Electric furnace melted, ladle refined & vacuum degassed and having a chemical composition (expressed in weight percentages):

- Carbon 0.23-0.28,
- Silicon 0.05-0.20,
- Manganese 1.20-1.60,
- Nickel not greater than 1.0,
- Sulfur not greater than 0.007,
- Phosphorus not greater than 0.020,
- Chromium 1.0-2.5,
- Molybdenum 0.35-0.80,
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm;

(b) With a Brinell hardness measured in all parts of the product including mid thickness falling within one of the following ranges:

- (i) 270-300 HBW,
- (ii) 290-320 HBW, or
- (iii) 320-350HBW;

(c) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.0, C not exceeding 0.5, D not exceeding 1.5; and

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 2 mm flat bottom hole;

(6) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:

(a) Made from Electric Arc Furnace melted, Ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):

- Carbon 0.23-0.28,
- Silicon 0.05-0.15,
- Manganese 1.20-1.50,
- Nickel not greater than 0.4,
- Sulfur not greater than 0.010,
- Phosphorus not greater than 0.020,
- Chromium 1.20-1.50,
- Molybdenum 0.35-0.55,
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm;

(b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.5, C not exceeding 1.0, D not exceeding 1.5;

(c) Having the following mechanical properties:

(i) With a Brinell hardness not more than 237 HBW measured in all parts of the product including

mid thickness; and having a Yield Strength of 75ksi min and UTS 95ksi or more, Elongation of 18% or more and Reduction of area 35% or more; having charpy V at -75 degrees F in the longitudinal direction equal or greater than 15 ft. lbs (single value) and equal or greater than 20 ft. lbs (average of 3 specimens) and conforming to the requirements of NACE MR01-75; or

(ii) With a Brinell hardness not less than 240 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 90 ksi min and UTS 110 ksi or more, Elongation of 15% or more and Reduction of area 30% or more; having charpy V at -40 degrees F in the longitudinal direction equal or greater than 21 ft. lbs (single value) and equal or greater than 31 ft. lbs (average of 3 specimens);

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and

(e) Conforming to magnetic particle inspection in accordance with AMS 2301;

(7) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:

(a) Made from Electric Arc Furnace melted, ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):

- Carbon 0.25-0.30,
- Silicon not greater than 0.25,
- Manganese not greater than 0.50,
- Nickel 3.0-3.5,
- Sulfur not greater than 0.010,
- Phosphorus not greater than 0.020,
- Chromium 1.0-1.5,
- Molybdenum 0.6-0.9,
- Vanadium 0.08 to 0.12
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm.

(b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.0(t) and 0.5(h), B not exceeding 1.5(t) and 1.0(h), C not exceeding 1.0(t) and 0.5(h),

and D not exceeding 1.5(t) and 1.0(h);

(c) Having the following mechanical properties: A Brinell hardness not less than 350 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 145ksi or more and UTS 160ksi or more, Elongation of 15% or more and Reduction of area 35% or more; having charpy V at -40 degrees F in the transverse direction equal or greater than 20 ft. lbs (single value) and equal or greater than 25 ft. lbs (average of 3 specimens);

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and

(e) Conforming to magnetic particle inspection in accordance with AMS 2301.

At the time of the filing of the petition, there was an existing antidumping duty order on certain cut-to-length carbon-quality steel plate products from Korea. See Notice of Final Determination of Sales at Less Than Fair Value: Certain Cut-To-Length Carbon-Quality Steel Plate Products from Korea, 64 Fed. Reg. 73,196 (Dep't Commerce Dec. 29, 1999), as amended, 65 Fed. Reg. 6,585 (Dep't Commerce Feb 10, 2000) (1999 Korea AD Order). The scope of the antidumping duty investigation with regard to cut-to-length plate from Korea covers only (1) subject cut-to-length plate not within the physical description of cut-to-length carbon quality steel plate in the 1999 Korea AD Order, regardless of producer or exporter; and (2) cut-to-length plate produced and/or exported by those companies that were excluded or revoked from the 1999 Korea AD Order as of April 8, 2016. The only revoked or excluded company is Pohang Iron and Steel Company, also known as POSCO.

The products subject to the investigation are currently classified in the Harmonized Tariff Schedule of the United States (HTSUS) under item numbers: 7208.40.3030, 7208.40.3060, 7208.51.0030, 7208.51.0045, 7208.51.0060, 7208.52.0000, 7211.13.0000, 7211.14.0030, 7211.14.0045, 7225.40.1110, 7225.40.1180, 7225.40.3005, 7225.40.3050, 7226.20.0000, and 7226.91.5000.

The products subject to the investigation may also enter under the following HTSUS item numbers: 7208.40.6060, 7208.53.0000, 7208.90.0000, 7210.70.3000, 7210.90.9000, 7211.19.1500, 7211.19.2000, 7211.19.4500, 7211.19.6000, 7211.19.7590, 7211.90.0000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7214.10.0000, 7214.30.0010, 7214.30.0080, 7214.91.0015, 7214.91.0060, 7214.91.0090, 7225.11.0000, 7225.19.0000, 7225.40.5110, 7225.40.5130, 7225.40.5160, 7225.40.7000, 7225.99.0010, 7225.99.0090, 7226.11.1000, 7226.11.9060, 7226.19.1000, 7226.19.9000, 7226.91.0500, 7226.91.1530, 7226.91.1560, 7226.91.2530, 7226.91.2560, 7226.91.7000, 7226.91.8000, and 7226.99.0180.

The HTSUS subheadings above are provided for convenience and customs purposes only. The written description of the scope of the investigation is dispositive.

3. This investigation has been assigned investigation number A-580-887.

4. For imports of certain carbon and alloy steel cut-to-length plate from the Republic of Korea, CBP shall suspend liquidation of such shipments entered, or withdrawn from warehouse, for consumption on or after 11/14/2016. Effective 11/14/2016, CBP shall require, for such entries, a cash deposit equal to the margins for the producers and/or exporters listed below:

Producer and/or Exporter: POSCO and POSCO Daewoo Corporation

Case number: A-580-887-001

Cash deposit rate: 6.82 %

All Others

Case Number: A-580-887-000

Cash Deposit Rate: 6.82%

5. If any entries of this merchandise are exported by a firm other than the producer, then the following instructions apply:

A. If the exporter of the subject merchandise does not have its own rate but the producer has its own rate, the cash deposit or bonding rate will be the producer's rate.

B. Where neither the exporter nor the producer has its own rate or the producer is unknown, use the all-others rate of 6.82 percent to establish the cash deposit.

6. If there are any questions by the importing public regarding this message, please contact the Call Center for the Office of AD/CVD Operations, Enforcement and Compliance, International Trade Administration, U.S. Department of Commerce at (202) 482-0984. CBP ports should submit their inquiries through authorized CBP channels only. (This message was generated by OVI:MJH.)

7. There are no restrictions on the release of this information.

Alexander Amdur

Company Details

*Party Indicator Value:

I = Importer, M = Manufacturer, E = Exporter, S = Sold To Party